Garage Door Hardware



Aurora Door Hanger and Specialty Co.

Anrora, Illinois, U. S. A.

Mike Jochson 1987

.

.

Rect 11-25-1927

Garage Door Hardware



Catalogue No. 6

Aurora Door Hanger and Specialty Co.

Aurora, Illinois, U.S.A.






& Specialty Company

No. 2700

Sliding Folding Garage Door Hardware



Sliding Folding Garage Hardware allows the use of any part of or the entire opening. Hanger has both vertical and lateral adjustment and is always used on second door from jamb.

All sets are packed complete including three butt hinges for Jamb doors and three surface hinges for succeeding doors.

LIST PRICE — DETAIL OF PARTS

No. 2700 Hangers, each\$3.00	No. 2700 4" x 4" Butts Pr 50
No. 2700 Center Bracket, each	No. 2700 4" x 4" Sur. Hinges
No. 2700 Intermediate Bracket, each	No. 512 Bolt 6.00
No. 2700 End Bracket, each 1.00	No. 512 Jr. Bolt 3.00

LIST PRICE — COMPLETE SETS

No. 2700 2 door sets complete	\$14.50
No. 2700 3 door sets complete	
No. 2700 4 door sets complete (Two Track)	
No. 2700 5 door sets complete	30.00
No. 2700 6 door sets complete	27.00

This Hardware is made in 3 weights for Nos. 2, 3 or 4 Track.






& Specialty Company

No. 2700

Sliding Folding Garage Door Hardware



Sliding Folding Garage Door Hardware is used to advantage where the opening is continuous the entire length or breadth of building and can be used for 3, 4, 5, or 6 door openings, any combination of these openings or multiples of same. This arrangement gives a weather-proof fit in the same manner as a swinging house door. Doors should not exceed three feet in width. Track length for each unit should be two times the width of one door plus eight inches. Track can be adjusted in brackets so that doors can swing to any angle desired.










This Hardware is made in 3 weights for Nos. 2, 3 or 4 Track.

'⊏ູ

No. 2700

Sliding Folding Garage Door Hardware





The above illustration features a four door sliding-folding outfit, best adapted to an 8 to 12 ft .opening. It consists of 3 doors hinged together and attached to side jamb, when open the doors can be folded clear of the opening. The fourth door is hinged to opposite jamb and is used as service door.

This type of hardware permits the use of smaller doors in the opening thereby giving more clearance for the car.

LIST PRICE

No. 2700-4 Door Set Complete (1 Trk)..\$20.00

This Hardware is made in 3 weights for Nos. 2, 3 or 4 Track.






& Specialty Company

No. 2600

Sliding Folding Garage Door Hardware

For Doors Opening Out



The above illustration features a three-door sliding-folding outfit with doors operating out. This conveys an idea which can be applied to any one of the No. 2700 combinations, and is recommended, when lack of space prohibits operating the doors inside.

LIST PRICE - DETAIL OF PARTS

No.	2600	Hangers, each\$3.	.00	No.	2600	4" x 4" Butts, Pr	50
No.	2600	Center Brackets, each				Offset Surface Hinges	
No.	2600	Intermediate Bracket, each	.70	No.	512	Bolt 6.	00
No.	2600	End Bracket, each 1.	.00	No.	512	Jr. Bolt	00

LIST PRICE — COMPLETE SETS

No.	2600	2	door	sets	complete	\$14.50
					complete	
					complete	
No.	2600	5	door	sets	complete	30.00
Nο	2600	6	door	sets	complete	37.00

This Hardware is made in 3 weights for Nos. 2, 3 or 4 Track.





& Specialty Company


`ຕຸ

No. 2500

Sliding Folding Garage Door Hardware

Flat Track Type






The Flat Track Type of Sliding Folding Garage Door Hardware can be used to operate doors either in or out and can be installed in 2-Door Sets or 4-Door Sets to meet conditions equally as well as in the 3-Door Sets as featured above. This type of hardware is in-expensive and is designed for both 1 car and 2 car garages, having light weight doors.

LIST PRICE — COMPLETE SETS

No. 2500 2 door sets complete\$	7.00
No. 2500 3 door sets complete	7.75
No. 2500 4 door sets complete (2 Track)	16.00





& Specialty Company

۵,

Parallel Door Hardware



Parallel Door Hardware is used to advantage where the opening is continuous the entire length or breadth of building and can be used for any number of doors required.

PRICE LIST

No. 2 No. 8-2	Hangers, per pair. \$3.00 Track, per foot. \$\frac{1}{23}\frac{25}{25}\$ Brackets, each \$7\frac{7}{3}\frac{3}{5}\$.50 Weather Strip, per foot	For Doors from 1½" to 2½" thick, weighing from 200 to 400 pounds.	No. 282-S-1 No. 3 No. 8-3 No. 517-3		For Doors from 134" to 234" thick, weighing from 300 to 500 pounds.
	No. 222-S-1 No. 4	Hangers, per Track, per f Brackets, ea Weather Str per foot	$\begin{bmatrix} \text{oot} & .50 \\ \text{ch} & 1.00 \end{bmatrix}$	75830 For Doors 7568 from 2½" to 75167 weighing from 500 to 800 pounds.	

[7]

Floor Guide, each 1.50 75189

Discount.....

No. 514

No. 500

Offset Hinge - Surface Pintle



Designed for Garage or Warehouse doors where it is desired they swing back of jamb thus allowing use of full width of opening.


Size of Strap	7573	List Price
Size of Strap 2½" x ½" x 18"	\$3.75	per pair
2½" x ¼" x 24"	4.25	per pair

Aurora Barn and Garage Hangers

No. 102-S-1 No. 102-S-2



No. 102-2



Used on doors $1\frac{3}{4}$ " thick to $2\frac{1}{2}$ " thick. Wheels grey iron $2\frac{1}{8}$ " in diameter. Double Apron. Front apron 6" long, $3\frac{1}{2}$ " wide. One pair of hangers consists of 2 hangers, 1 center, and two end brackets, lag bolts for brackets, carriage and stove bolts for hangers. Packed one dozen pair in crate. Weight 10 pounds per pair. Track $1\frac{3}{4}$ pounds per foot.


			List Price	_
ME	all No.	102-S-1	Hangers with 3 brackets, per pair (Roller Bearing))
1-	No.	102-S-2	Hangers with 3 brackets, per pair (Ball Bearing))
	No.	102 - 2	Hangers with 3 brackets, per pair (Roller Bearing))
	No.	2	Track 4, 6, 8, and 10 ft. lengths, per foot	5
	No.	9-2	Brackets, each	3





& Specialty Company






Cane Bolt

Cane Bolts are used to hold swinging doors in either an open or closed position.

Can also be used on Sliding Folding doors for the same purpose and can be used to lock sliding doors in a closed position from the inside.

Aurora Iron Duke Trolley Hanger

No. 222-2



Distance from top of door to center of hole in bracket according to adjustment varying from 7 1/8 to 9 3/4 inches.

Used on doors $2\frac{3}{8}$ to $3\frac{1}{2}$ inches thick. Track can be attached to side or ceiling supports. Wheels, grey iron, 3 inches in diameter. Roller bearing. Aprons double. Front apron 12 inches long, $4\frac{1}{2}$ inches wide and 3/16 inch thick. A pair of hangers consists of two hangers with stove and carriage bolts in individual box.


Weight—Hangers, per pair, 24 pounds. Track, per foot, 4 pounds. Packed 6 pairs in crate.

LIST PRICES

No. 222-2 Hangers, with bolts per pair\$	6.00
No. 4 Track, 4, 5, 6, 8, and 10-foot lengths, per foot	
No. 9-4 Brackets, each	.44







No. 68

A good heavy all steel combination thumb latch and pad lock attachment can be used on right or left hand doors also on one ply or heavier doors. Packed, one latch complete with screws in metal edge box.

List PriceEach \$.50

No. 525 — Binders

Stock 1/4" x 2"

						List Price
No.	525-1	for	13/4"	door	per	doz\$2.70
No.	525-2	for	2 "	door.	per	doz 2.80
No.	525-3	for	21/4"	door	per	doz 2.80
No.	525-4	for	3 "	door	per	doz 3.00





Handles


A good substantial raised handle made of steel in two sizes.

No	0.405-01	Weight	per doze	en	 	 	$2\frac{1}{4}$	ounds
No	. 405-11	Weight	per doze	en	 	 	. 5 r	ounds
			1				1	
							Li	st Price
No	. 405-01				 	 	Eac	h \$.10
No	405-11						Eac	h 15

Floor Door Guides and Stops

No. 514

Adjustable Floor Guide for Parallel Doors



Used with parallel sliding doors to guide and hold in place.

Adjustable for doors 11/2" to 3". Weight 4 pounds.

No. 513

Cast Floor Guide and Stop




Made in 2 sizes to guide and stop doors at center of opening.

No. 513-1 For 3-ply doors.....Each \$.75
No. 513-2 For 2-ply doors.....Each .60

No. 515

Adjustable Floor Guides for Center Bump Doors




Used where doors bump together to guide and hold in place.

Adjustable for doors $1\frac{1}{2}$ " to 3". Weight 2 pounds.

List priceEach \$.80

No. 516

Adjustable Floor Guide and End Stops



Used as guide and end stop, right angle doors or regular sliding doors.

Adjustable for doors 13/4" to 3". Weight 2 pounds.

List price Each \$.60

No. 405—12 Bumper Shoes (two per set): List price, each \$.10

Up and Down Bolt



Easily operated. Can be used on any swinging door. Has Center interlocking device Malleable Iron Plungers. Keepers furnished are for Flush Doors. Special keepers furnished to suit conditions at small extra charge.

DIRECTIONS FOR INSTALLING

Fasten Bolt cages to top and bottom of doors and interlocking device in center. Place interlocking device in open position and the top and bottom plungers in keepers and connect with chain.

List price\$3.00

No. 512

Up and Down Bolt

Made in one size for doors swinging either in or out, and can be used for doors of any height. Packed in a small package with all screws and necessary parts. Has perfect interlocking device, which when released will act as door holder. Chain is used for the adjustment of bolt to various heights of doors. When the interlocking device is released, bolts shoot into position at both top and bottom, and the door is positively locked. Two top keepers furnished with bolt for doors swinging either in or out. Special keepers can be furnished to meet conditions for a slight extra charge. Keepers furnished regularly are for flush doors.

DIRECTIONS FOR INSTALLING

First fasten bolt and interlocking device to door, then place interlocking device in open position, and the top and bottom plungers in the top and bottom keepers. Chain is fastened by S hook. For any further adjustment use thumb bolts in plungers where 3/4" adjustment is provided for.

Packed one complete in box.

